UNITED OIL COMPANY

Quality Industrial Lubricants Since 1906

1800 North Franklin Street

Pittsburgh, Pennsylvania 15233

PH: (412) 231-1269 FX: (412) 231-1384

Pneumatic RockDrill - #220 & #320 Heavy Duty, Biodegradable DTH Fluid

Product Data Sheet

Product Description:

Pneumatic RockDrill #220 & #320 are an ultimately biodegradable(Pw1), extra heavy duty rock drilling fluid engineered to meet the demanding requirements of air drilling. RockDrill is formulated with a high viscosity, renewable base oil with additives which in part anti-wear properties and promote corrosion resistance. The natural polarity of the fluid allows the fluid to adhere to metal tooling surfaces while exposed to highly compressed air.

Outstanding Qualities:

- 1. Environmentally friendly fluid optimized for DTH Hammers
- 2. Anti- wear and extreme pressure protection
- 3. Corrosion and rust protection
- 4. High viscosity index fluid with temperature stability
- 5. Superior metal adhesion decreases wear and shanking

Technical Information:

ISO Grade		# 220	# 320
SAE Grade		50	N/A
Specific Gravity	ASTM D1298	.958	.924
Viscocity Index	ASTM D2270	203	206
Biodegradablity %	ASTM D5864	Pw1> 80%	Pw1 > 80%
Copper Corrosion	ASTM D4048	1 A	1 A
Rust Test A & B	ASTM D665	Pass	Pass
Pour Point	ASTM D97	18° F	23° F
Flash Point	ASTM D92	588° F	588° F
Falex Timken EP	ASTM D2782	70 ibs	70 lbs
Falex Extreme Pressure	ASTM D3233	3,500 lbs	3,500 lbs

Available Packaging

55 Gallon Steel or Plastic Drums 275 Gallon Totes

